

POWERFIX EPOXY

DESCRIPTION

Powerfix-EPOXY is three components Epoxy based joint filler. It is easily applicable in the joints of vitrified tiles, glass mosaic tiles and other tiles. Also, it is suitable for the joints of granite, natural stone, composite marble and quartz stone. The excellent feature of Powerfix-EPOXY is that, it can easily be cleaned from any surface with water and scrubber/scotch brite within stipulated time.

PROCEDURE

Powerfix-EPOXY grout is ideally suited for residential and commercial installation where the materials must resist physical abuse, stains, spillage and chemical attack. Powerfix-EPOXY grout is applied in grooves of tiles used in kitchen, bathrooms, restaurants, cafeterias, light industrial applications and high traffic areas.

BENEFITS

- Stain free • Temperature resistant
- Easy to install and clean
- Durable & Hard joints
- Cleanable with water • Color fast
- Stain and bacterial resistant
- Non cracking and powdering
- Hygienic and chemical resistant
- Waterproofing and durable finish
- High strength and versatile



PACKING & RATIO

For 1 kg - Base (180 gm), Hardener (90 gm) & Epoxy Filler (730 gm)

For 5 kg - Base (900 gm), Hardener (450 gm) & Epoxy Filler (3.650 gm)

1 kg/ 5 kg



Coverage: Varies as per width & depth of joint

Tile Size (mm)	Tile Thickness (mm)	Joint Width (mm)	Coverage (kg/sq.mtr.)
300 x 300	7	2	0.15 kg/m ²
600 x 300	8	5	0.32 kg/m ²
450 x 300	7	5	0.31 kg/m ²
600 x 600	8	5	0.21 kg/m ²
Mixing Ratio (By Weight in grams)			
Base	Hardener	Filler	
180g	90g	730g	

How to mix ?

