

Durga Bondchem Private Limited

Regd. Office: F-01, Surdhara Flats & Shops, Near Panchsheel Vidyalaya B/h. Sarswati Complex, Manjalpur, Vadodara-390 011 Gujarat, India CIN No.: U24100GJ2015PTC083583

POWERFIX READY MIX PLASTER

DESCRIPTION

Powerfix Ready Mix Plaster is strong pre-mixed powder/render with high quality polymer additives, suitable for plastering all types of concrete surfaces (old and new), clay bricks, fly ash bricks and AAC blocks. It is normally applied to masonry interiors and exterior to achieve a smooth and even surface. Powerfix-Readymix plaster contains processed and fine graded sand which gives better quality of plaster.

ADVANTAGES

- Create a leveled surface from uneven masonry or concrete wall
- Basic leveling of concrete, light weight blocks and bricks.
- Filling holes and irregularities, leveling walls and ceiling.
- Under coating and plastering over existing concrete and brick/block walls.
- Last rebound loss in comparison to traditional plastering.

SURFACE PREPARATION

- Dirt, soil and roof runoff stains from the surface should be removed.
- Start at the top and wash the dirt (pre-wetting of surface) down the wall before applying plaster.



40 kg

PREPARATION

- Take a small amount of water in bucket and gradually add Powerfix-readymix plaster in it. Mix the
 product with approximately 18% to 20% of water (as per weight).
- Mixing can be done manually or by the electrical stirrer (for better result) till homogenous mix is obtained.
- After proper mixing leave the paste for 5-10 min for polymeric dispersion before application.
- Use mixture within 1 hour of preparation of mix. Hard & set plaster should not be mixed again.
- Correct ratio of water and readymix plaster is essential for better results.



MIXING RATIO

Add 300-350 ml water in 1 kg Powerfix Readymix Plaster.