

POWERFIX GROUT

DESCRIPTION

Powerfix-Tile Grout is composed of precisely graded, pure crystalline, marble powder, a blend of special cements, water repellent materials, oxide colors and plasticizers. Powerfix-Tile Grout does not curl up during application and gives a wear and weather resistant joint with no shrinkage cracks.

PROCEDURE

Apply Powerfix-Tile Grout diagonally into the joints with a rubber edged spatula. Remove excess grout with a moist sponge before drying.

Do not apply grout to an area, which is so large that cannot be completed within an hour. Porous tiles should be moistened with water before grouting.

After the grout has dried and before it has hardened, polish the tiles with a clean, dry cloth leaving the joints flush with the tiles. moistened the joints with a wet sponge after 24 hours of grouting.

BENEFITS

Powerfix-Tile Grout is hard wearing, water resistant grout for filling joints in interior exterior wall, floor tiles and stones up to 5 mm width.

It is easily applied and does not shrink when dry.

SURFACE PREPARATION

Before applying Powerfix-Tile Grout, clean the joints and edges of tiles and ensure that it is free of excess tile fixing mortar.



500 g / 1 kg



MIXING

Thoroughly mix Powerfix-Tile Grout in the ratio of 1 liter Water to 3 kg Powerfix-Tile Grout powder. Allow it to stand for 15 minutes before using. Stir again before use.