

TECHNICAL DATA SHEET

Trade Name	Compound Ferric Green			
Type	S835			
Delivery Form	Powder			
Colour Index	Combination Of Pigment Yellow 42 & Blue 15:3			
Cas No./Ec No.	20344-49-4, 147-14-8, 471-34-1			
Specification	Contents	%		ISO1248
	Oil Absorption	ml / 100g	25~35	ISO787-5
	Res. On 325#	%	≤ 0.3	ISO787-5
	Water Soluble Salts	%	≤ 3.0	ISO787-5
	Moisture	%	≤ 1.0	ISO787-2
	pH VALUE		6 ~ 9	ISO787-9
	Loss On Ignition (1000 ⁰ c, 30 Min)	%		DIN 55913
	Bulk Density	g /cm ³	0.6 ~ 0.9	ISO787-11
	Specific Gravity	g /cm ³		ISO787-10
	Tinting Strength (Compared With Standard)	%	95 ~ 105	ISO787-21
	Color Difference ΔE (Compared With Standard)		≤ 1.5	ISO787-1
Packing Style	In 25 Kg Paper Bag			
Transport & Storage	Protect Against Weathering / Store In Dry Place, Temperature Of Above 80 ⁰ c Must Be Avoided			
Safety	The Product Is Not Classified As Hazardous Under EC 1907/2006 & EC 1272/2008			